

Fortinet® Transceivers

Transceiver Modules for Fortinet Products

Fortinet's range of pluggable copper and optical transceiver modules are designed to complement Fortinet appliances that support transceiver module slots, including the FortiGate®, FortiSwitch™ and other appliance platforms.

Take the guesswork out of selecting transceivers

Common connectivity problems in enterprise and data center networks are often traced back to low-quality and incompatible transceiver modules, rather than a fault in the network appliances themselves. Fortinet's transceivers have been purpose-built and tested to work with Fortinet equipment, ensuring that your network is as stable and robust as possible, and taking the guesswork out of selecting compatible transceivers.

Wide range for maximum flexibility

Supporting various form factors, media types and throughput, Fortinet transceivers provide connectivity options to meet many different network architectures and deployment scenarios. Whether your network demands high-speed 100 GE inside the data center, or long-range 1 GE to connect data centers in different cities, Fortinet has a transceiver to meet your needs.

High-Performance Transceiver Modules for High-Performance Network Security Appliances

- Copper and optical options
- Supports SFP, SFP+, QSFP+, DAC and CFP2 slots
- Performance from 1 Gbps to 100 Gbps
- Tested for compatibility with Fortinet appliances

Key Features & Benefits

Various Interface Options	Fortinet transceivers support various interfaces, including: SFP, SFP+, DAC and newer high-speed standards including QSFP+ and CFP2.
Tested for Compatibility	You can rest assured that your Fortinet transceivers have been tested for compatibility on Fortinet products, taking the guess-work out of selecting transceivers for your environment.
Maximize Network Uptime	Eliminate connectivity problems to maximize network uptime by using quality transceivers, designed to work with Fortinet products.
Cost Effective	Transceiver modules can be expensive, especially those with sensitive high-speed optics. Fortinet delivers high-quality transceivers, while keeping cost to a minimum.



SPECIFICATIONS

	FG-TRAN-GC	FG-TRAN-SX	FG-TRAN-LX	FG-TRAN-SFP+SR	FG-TRAN-SFP+LR	FG-TRAN-QSFP+SR
Hardware Specifications						
Protocol Standard	1000Base-T	1000Base-SX	1000Base-LX	10GBase-SR	10GBase-LR	40GBase-SR4
IEEE Standard	802.3ab	802.3z	802.3z	802.3ae	802.3ae	802.3ba
Module Type	SFP	SFP	SFP	SFP	SFP+	QSFP+
Hot Plug	Yes	Yes	Yes	Yes	Yes	Yes
Data Link Rate for Ethernet	1.25 Gbps	1.25 Gbps	1.25 Gbps	10 Gbps	10 Gbps	1.06 Gb/s–41.2 Gbps
Media	copper interface	MM	SM	MM	SM	SM
Wavelength (nm)		850	1310	850	1310	750–980 nm
Laser Type	NA	vcSEL	Fabry Perot	vcSEL	CWDM DFB laser, PIN receiver	VCSEL (4channel), PIN
Transmit Power (dBm)		min = -9, max = -1	min = -9.5, max = -3.0	min = -4.3, max= -1	min = -8.2, max = 0.5	min = -7.6, max = -1
Receive Power (dBm)		receiver sensitivity = -19	receiver sensitivity = -20	receiver sensitivity = -11.1	receiver sensitivity = -12.6	receiver sensitivity = -5.4
Connector Type	RJ-45	Duplex LC	Duplex LC	Duplex LC	Duplex LC	Single 1x12 MPO
Power Dissipation	1.05 W	<800 mw	< 830 mw	600 mw	850 mw	<1.5 W
Transmission Range	100 m	220 m / 500 m	10 km	300 m	10 km	100 m (OM3)–150 m (OM4)
Operating Temperature Range	0–85°C	0–70°C	0–70°C	0–70°C	0–85°C	0–70°C
Serial ID PROM	Yes	Yes	Yes	Yes	Yes	yes
Digital Monitoring	No	No	Yes	Yes	Yes	yes
Auto Negotiation	Yes	NA	NA	NA	NA	NA
Link Status	Yes	Yes	Yes	Yes	yes	yes

	FG-TRAN-QSFP+LR	SP-CABLE-ADASFP+	FG-TRAN-CFP2-SR10	FG-TRAN-CFP2-LR4	FG-TRAN-XFP-SR	FG-TRAN-XFP-LR
Hardware Specifications						
Protocol Standard	40Gbase-LR4	DAC	100GBase-SR10	100GBase-LR4	10GBase-SR	10GBase-LR
IEEE Standard	802.3ba		802.3ba	802.3ba	802.3ae	802.3ae
Module Type	QSFP+		CFP2	CFP2	XFP	XFP
Hot Plug	Yes		Yes	Yes		
Data Link Rate for Ethernet	41.2 Gbps	1 G–10 Gbps	103.12 Gbps	103.1 Gbps		
Media	SM		MM	SM	MM	SM
Wavelength (nm)		NA	850	1310	850	1310
Laser Type	4x 10 G uncooled CWDM (DFB)	NA	VCSEL (10 channel), PIN	4x 26 Gb DFB LAN-WDM laser	VCSEL	EML laser, PIN
Transmit Power (dBm)	min = -4.8, max = 8.3				min = -7.3, max = -1	min = -6.0, max = -1
Receive Power (dBm)	receiver sensitivity = -11.5				receiver sensitivity = -11.1	receiver sensitivity = -14.4
Connector Type	Duplex LC	SFP+ card edge connector	24 fiber MPO	Duplex LC	Duplex LC	Duplex LC
Power Dissipation	<3.5 W			<8 W	1.5 W	<2.5 W
Transmission Range	10 km	.5 m–15 m	100 m (OM3)–150 m (OM4)	10 km	300 m (OM3)	10 km
Operating Temperature Range	0–70°C		0–70°C	0–70°C	0–70°C	0–70°C
Serial ID PROM	Yes	Yes	Yes	Yes	Yes	Yes
Digital Monitoring	Yes	Yes	Yes	Yes	Yes	Yes
Auto Negotiation	NA	NA	NA	NA	NA	NA
Link Status	yes		Yes	Yes	Yes	Yes

ORDER INFORMATION

Product	SKU	Description
1 GE SFP LX transceiver module	FG-TRAN-LX	1 GE SFP LX transceiver module for all systems with SFP and SFP/SFP+ slots
1 GE SFP RJ45 transceiver module	FG-TRAN-GC	1 GE SFP RJ45 transceiver module for all systems with SFP and SFP/SFP+ slots
1 GE SFP SX transceiver module	FG-TRAN-SX	1 GE SFP SX transceiver module for all systems with SFP and SFP/SFP+ slots
10 GE SFP+ transceiver module, short range	FG-TRAN-SFP+SR	10 GE SFP+ transceiver module, short range for all systems with SFP+ and SFP/SFP+ slots
10 GE XFP transceiver module, short range	FG-TRAN-XFPSR	10 GE XFP transceiver module, short range for all systems with XFP slots
10 GE SFP+ transceiver module, long range	FG-TRAN-SFP+LR	10 GE SFP+ transceiver module, long range for all systems with SFP+ and SFP/SFP+ slots
10 GE XFP transceiver module, long range	FG-TRAN-XFPLR	10 GE XFP transceiver module, long range for all systems with XFP slots
40 GE QSFP+ transceivers, short range	FG-TRAN-QSFP+SR	40 GE QSFP+ transceivers, short range for all systems with QSFP+ slots
40 GE QSFP+ transceivers, long range	FG-TRAN-QSFP+LR	40 GE QSFP+ transceivers, long range for all systems with QSFP+ slots
10 GE SFP+ active direct attach cable, 10m / 32.8 ft	SP-CABLE-ADASFP+	10 GE SFP+ active direct attach cable, 10m / 32.8 ft for all systems with SFP+ and SFP/SFP+ slots
100 GE CFP2 transceivers, long range	FG-TRAN-CFP2-LR4	100 GE CFP2 transceivers, long range, over single mode fiber, for all systems with CFP2 slots
100 GE CFP2 transceivers, short range	FG-TRAN-CFP2-SR10	100 GE CFP2 transceivers, 10 channel parallel fiber, short range for all systems with CFP2 slots



GLOBAL HEADQUARTERS	EMEA SALES OFFICE	APAC SALES OFFICE	LATIN AMERICA SALES OFFICE
Fortinet Inc. 899 Kifer Road Sunnyvale, CA 94086 United States Tel: +1.408.235.7700 Fax: +1.408.235.7737	120 rue Albert Caquot 06560, Sophia Antipolis, France Tel: +33.4.8987.0510 Fax: +33.4.8987.0501	300 Beach Road #20-01 The Concourse Singapore 199555 Tel: +65.6513.3730 Fax: +65.6223.6784	Prol. Paseo de la Reforma 115 Int. 702 Col. Lomas de Santa Fe, C.P. 01219 Del. Alvaro Obregón México D.F. Tel: 011-52-(55) 5524-8480

Copyright© 2014 Fortinet, Inc. All rights reserved. Fortinet®, FortiGate®, FortiCare® and FortiGuard®, and certain other marks are registered trademarks of Fortinet, Inc., and other Fortinet names herein may also be registered and/or common law trademarks of Fortinet. All other product or company names may be trademarks of their respective owners. Performance and other metrics contained herein were attained in internal lab tests under ideal conditions, and actual performance and other results may vary. Network variables, different network environments and other conditions may affect performance results. Nothing herein represents any binding commitment by Fortinet, and Fortinet disclaims all warranties, whether express or implied, except to the extent Fortinet enters a binding written contract, signed by Fortinet's General Counsel, with a purchaser that expressly warrants that the identified product will perform according to certain expressly-identified performance metrics and, in such event, only the specific performance metrics expressly identified in such binding written contract shall be binding on Fortinet. For absolute clarity, any such warranty will be limited to performance in the same ideal conditions as in Fortinet's internal lab tests. Fortinet disclaims in full any covenants, representations, and guarantees pursuant hereto, whether express or implied. Fortinet reserves the right to change, modify, transfer, or otherwise revise this publication without notice, and the most current version of the publication shall be applicable.